I claim:

5

15

1. A method for reducing a program, M, that preserves at least one branching time property, f, comprising the steps of:

forming a product of said program, M and said branching time property, f, expressed as an automaton, f;

obtaining an abstract domain containing a set of abstract values to generalize possible states of said program and abstract relations that relate said program states to said abstract domain;

computing an abstract program with a reduced number of states and an altered version of said branching time property, f, using said product.

- 2. The method of claim 1, further comprising the step of performing an automated program check.
- 3. The method of claim 2, wherein said automated program check is a model checking step.
- 4. The method of claim 3, wherein said automated program check is performed for an altered branching time property.
 - 5. The method of claim 1, wherein said computing step further comprises the step of defining a set of states, S', in said abstract program as $S' = \overline{S} \times Q$, where S is a set of states in said program, M, and Q is a finite set of states.
 - 6. The method of claim 5, wherein OR states in said set of states, S', are those states where $\delta(q,true)$ has the form $q_1 \vee q_2$ or $\langle a \rangle q_1$, and all other states are AND states, where q are individual states and δ is a transition relation between states.

25

7. The method of claim 5, wherein an abstract state (t,\hat{q}) is in a subset of initial states, I', of the abstract program if there exists $s \in I$ for which $s\xi_{\hat{q}}t$, where s is an individual state, I is a subset of initial states, I, of the program, M, and $\xi_{\hat{q}}$ is one of said abstract relations.

5

- 8. The method of claim 5, wherein for an abstract AND state (t, q), the transition ((t, q); (t', q')) is in an abstract transition relation, R', if there exists a concrete state (s, q) and a successor (s', q') that are related to (t, q); (t', q') respectively.
- 10 9. The method of claim 5, wherein for an abstract OR state (t, q), the transition ((t, q); (t', q')) is in an abstract transition relation, R', only if for every (s, q) which is related to (t, q), there exists a successor (s', q') which is related to (t', q').
- 10. The method of claim 8, wherein said product ATS $M \times A$ is abstracted by weakening said transition relations at AND states.
 - 11. The method of claim 9, wherein said product ATS $M \times A$ is abstracted by strengthening said transition relations at OR states.
- 20 12. The method of claim 8, further comprising the step of obtaining one or more rank functions and employing said one or more rank functions in an abstract transition relation, R'.
- 13. The method of claim 8, further comprising the step of obtaining one or more choice predicates and employing said one or more rank functions in an abstract transition relation, R'.
 - 14. A system for reducing a program, M, that preserves at least one branching time property, f, comprising:
- a memory; and

a processor operatively coupled to said memory, said processor configured to:

form a product of said program and said branching time property;

obtain an abstract domain containing a set of abstract values to generalize possible states of said program and abstract relations that relate said program states to said abstract domain;

5

15 -

25

30

compute an abstract program with a reduced number of states and an altered version of said branching time property using said product.

- 10 15. The system of claim 14, wherein said processor is further configured to perform an automated program check.
 - 16. The system of claim 15, wherein said automated program check is a model checking step.
 - 17. The system of claim 16, wherein said automated program check is performed for an altered branching time property.
- The system of claim 14, wherein said processor is further configured to
 define a set of states, S', in said abstract program as S' = \overline{S} \times Q, where S is a set of states in said program, M, and Q is a finite set of states.
 - 19. The system of claim 18, wherein OR states in said set of states, S', are those states where $\delta(q, true)$ has the form $q_1 \vee q_2$ or $\langle a \rangle q_1$, and all other states are AND states, where q are individual states and δ is a transition relation between states.
 - 20. The system of claim 18, wherein an abstract state (t,\hat{q}) is in a subset of initial states, I', of the abstract program if there exists $s \in I$ for which $s\xi_{\hat{q}}t$, where s is an individual state, I is a subset of initial states, I, of the program, M, and $\xi_{\hat{q}}$ is one of said abstract relations.

- The system of claim 18, wherein for an abstract AND state (t, q), the transition ((t, q); (t', q')) is in an abstract transition relation, R', if there exists a concrete state (s, q) and a successor (s', q') that are related to (t, q); (t', q') respectively.
- The system of claim 18, wherein for an abstract OR state (t, q), the transition ((t, q); (t', q')) is in an abstract transition relation, R', only if for every (s, q) which is related to (t, q), there exists a successor (s', q') which is related to (t', q').
- 23. The system of claim 21, wherein said product ATS $M \times A$ is abstracted by weakening said transition relations at AND states.
 - 24. The system of claim 22, wherein said product ATS $M \times A$ is abstracted by strengthening said transition relations at OR states.
- 15 25. The system of claim 21, further comprising the step of obtaining one or more rank functions and employing said one or more rank functions in an abstract transition relation, R'.
- 26. The system of claim 21, further comprising the step of obtaining one or more choice predicates and employing said one or more rank functions in an abstract transition relation, R'.